



Manufacturers of BIO-SAFE Technology

## Application Data Sheet:

# AQUACRYL

## WATER BASED GLAZE COAT

---



### APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** to determine the ease of application and desired results that will meet YOUR requirements.
- Surface must be clean and dry before application
- AQUACRYL can be recoated if they are clean and sound
- Allow new surfaces to cure for at least 7 days prior to application
- AQUACRYL is not suitable for very low or non-absorbent surfaces such as tessellated or glazed tiles
- Avoid applying on areas prone to rising damp
- Use brush, broom or applicator pad
- Apply 2-3 thin, even coats of AQUACRYL depending on the porosity of the surface and finish required.
- Do not apply if air surface temperature is below 10 degrees C.
- Allow 2-4 hours between coats
- Keep heavy traffic off final coat for 24 hours
- Ensure that the surface is not wetted for 24 hours after sealing

---

#### Disclaimer – User Guide

Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or

*misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user MUST educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*

Solutions - Sealers Technical service department Doc: AGGRO APPLICATION DATA.VER.2