



SOLUTIONS

SEALERS FOR STONE & TILE
The Next Generation of Stone Care Products

NATIONAL PH: 1300 4 STONE

Ph. + 61 7 5437 7714

Fax: + 61 7 5437 7715

E: info@solutionssealers.com.au

W: www.solutionssealers.com.au


ABN: 25 128 656 082

Manufacturers of BIO-SAFE Technology

Technical Data Sheet:

QUANTUM BIO-REDUCED™

COMMERCIAL GRADE SEALER



Description:

QUANTUM BIO-REDUCED™ is the ultimate stain protection for the professional applicator sealing porous stone, pavers and tiles. The stain protection and long life of QUANTUM BIO-REDUCED™ is specifically designed for the high performance demand market.

Advantages:

- Penetrating breathable sealer
- Uses a blend of BIO-SAFE™ solvents
- High repellence against oils, food products & water
- Over 90% reduction in water uptake, reducing moss & mould growth
- Excellent salt resistance
- Reduces salt efflorescence & freeze thaw
- Minimal change to substrate appearance
- Excellent on porous surfaces & polished concrete

Characteristics:

Colour:	Clear
Weight	0.86
Solvent	N-Butyl Acetate
DG Class	3
U.N Number	1263
Coverage	2 – 6 sq m per lt (depending on porosity)

Recommendations:

Sandstone
Terracotta
Clay & Concrete Pavers
Porous Granite & Limestone

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*