



Manufacturers of BIO-SAFE Technology

Application Data Sheet:

AGGRO

SEALER STRIPPER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** to determine the ease of application and desired results that will meet YOUR requirements.
 - Apply a thick even coat of **AGGRO** to surface area with brush, mop or spray.
 - Let stand for approx 60 minutes, (time may vary depending on temperature and thickness of sealer) before agitating with a stiff brush or an abrasive synthetic scrubbing pad to loosen any dissolved coating. (The thicker the coating the longer you should wait before agitating.)
 - DO NOT allow **AGGRO** to dry on surface, keep moist with more products.
 - DO NOT use in temperatures over 35deg.C
 - Once dissolved, remove the coating with a scraper squeegee, cotton mop, wet vacuum or extractor etc.
 - Rinse off all excess **AGGRO** thoroughly. (Externally it may be practical to blow the coating off with a high pressure water blaster.)
 - More than one application maybe necessary to totally remove coating residue.
 - Ensure that the resin and stripper are disposed of in accordance with local council requirements.
-

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*