



Manufacturers of BIO-SAFE Technology

## Application Data Sheet:

# CONSOLIDATE

## STONE SEALER

---



### APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Ensure surfaces are DRY, clean and free from grout haze, dirt and other residue.
- Do not thin this product.
- Generously saturate the surface using a low surface hand spray, a clean brush, or similar.
- The surface should have a 'wet look' for 5-10 seconds. Avoid contact with surrounding areas. After 10-15 minutes, re-apply product.
- After final coat, allow 10 minutes to penetrate surface then polish off any excess with a clean, lint free white cotton cloth.
- For best results, after 24-48 hours curing time, application of surface sealer or stain resistant sealer may be applied depending on substrate e.g. PRISTINE, PLUS or QUANTUM.
- If sealing POOLCOPING, discuss with pool builder options of dip sealing, skim coating adhesive and/or water proofing membrane. (Tensile tests performed on sealed stone have been successful using MAPEI grani-rapid on SANDSTONE)
- DIP SEALING - pour product into tray at a depth to cover stone to be sealed. Dip stone into solution for approximately 15-20 seconds. Remove and wipe off excess product with a clean, lint free white cotton cloth. Allow to dry for 24-48 hours before adhesion.
- Clean equipment with an organic solvent.

---

### Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user MUST educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*