



Application Data Sheet:

D-SCALE

PHOSPHORIC ACID CLEANER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** for suitability on surface. Pour small amount of **D-SCALE** on an inconspicuous area and leave for 5 minutes. Check for any surface damage or any other adverse reactions.
- Sweep or vacuum area to remove all dirt and loose debris.
- Before applying solution, soak area with water - particularly grout joints, so that solution is applied to an already wet surface.
- With a clean rag, sponge or synthetic mop, apply solution to the surface leaving it to act for a few minutes only.
- Use a scrubbing brush, stiff broom or floor washing machine (with nylon or natural bristles) to agitate, ensuring that the acid does not dry on the surface.
- Clean up residue with cloth or liquid vacuum cleaner.
- Scrub with clean brush to bring acid residue to the surface.
- Rinse with lots of water to neutralize acid. (For best results use **NATURAL CLEAN**) and remove any residue.
- **Dilute** 3 parts **D-SCALE** to 10 parts water. (Reduce amount of water for increased effectiveness).

WARNING:

INCREASED **D-SCALE** MAY DAMAGE/WEAKEN GROUT JOINTS.

D-SCALE IS NOT TO BE USED ON ACID SENSITIVE SURFACES LIKE MARBLE, TRAVERTINE, SOME LIMESTONES & GRANITES, TERRAZZO AND GLAZED TILES.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*