



Manufacturers of BIO-SAFE Technology

Application Data Sheet:

EASI-SEAL

PENETRATING SEALER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
 - Remove all dirt, stains, detergent, and efflorescence, acid, cement residue or previously applied sealers.
 - Wait at least 24 hours after laying tiles or grouting.
 - Apply evenly with a sponge, brush, applicator, or sprayer. Avoid contact with skin.
 - Avoid overlapping, pooling, and rundown. Work fully into tiles.
 - Allow the sealer to penetrate for 3 – 5 minutes before absorbing any excess with a damp, clean rag or sponge.
DO NOT LEAVE EXCESS TO DRY ON SURFACE - a white film may form which is extremely difficult to remove.
 - **EASI-SEAL** takes 24 hours to cure, but can be walked on in 30 minutes.
 - Ensure the surface remains dry for at least 12 hours.
-

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*