




Manufacturers of BIO-SAFE Technology

## Application Data Sheet:

# ENVIRO

## SAFETY STRIPPER

---



### APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** to determine the ease of application and desired results will be achieved that will meet YOUR requirements.
- Apply a thick even coat of **ENVIRO** to surface area with brush or mop.
- Let stand for between 1 - 2 hours, before agitating with a stiff brush or abrasive synthetic scrubbing pad to loosen any dissolved coating.
- The thicker the coating the longer you should wait before agitating.
- **ENVIRO** can be left for up to 4 hours internally before it evaporates.
- Once dissolved, remove the coating with a scraper, squeegee, cotton mop, wet vacuum or extractor etc., before rinsing thoroughly.
- Externally, it may be practical to blow the coating off with a high pressure water blaster.
- More than one application maybe necessary to totally remove coating residue.
- Ensure that the resin and stripper are disposed of in accordance with local council requirements.

---

#### Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*