



SOLUTIONS

SEALERS FOR STONE & TILE
The Next Generation of Stone Care Products

NATIONAL PH: 1300 4 STONE

Ph. + 61 7 5437 7714

Fax: + 61 7 5437 7715

E: info@solutionssealers.com.au

W: www.solutionssealers.com.au

ABN: 25 128 656 082

Manufacturers of BIO-SAFE Technology

Application Data Sheet:

KICKAR

HEAVY DUTY ACID CLEANER



APPLICATION:

READ SAFETY DIRECTIONS BEFORE OPENING OR USING.

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** to determine suitability on surface being cleaned and desired results that will meet YOUR requirements.
- For light clean up, dilute 15-20 parts water: 1 part KICKAR.
- If stronger mix is required, use 5-10 parts of water: 1 part KICKAR.
- For stubborn build-up dilute KICKAR 50:50 with water.
- Apply with a consistent and even finish to effected area, leave for 1 – 2 minutes and then agitate to release contaminant.
- **DO NOT ALLOW KICKAR TO DRY BEFORE RINSING.**
- Rinse area thoroughly with 20 parts water: 1 part NATURAL CLEAN.
- FLOOD & FLUSH AREA WITH WATER, to remove all KICKAR from surface.
- Repeat NATURAL CLEAN rinse and water flush. (External areas rinse with a hose).
- Follow local council laws for runoff.

WARNING:

Highly corrosive. Contact with eyes even for short periods can cause blindness. Causes severe burns which are not likely to be immediately painful or visible. Read safety directions before opening or using.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user MUST educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*

Solutions - Sealers Technical service department Doc: KICKAR APPLICATION DATA.VER.2