




Manufacturers of BIO-SAFE Technology

Application Data Sheet:

PAVACRYL

HARD COAT



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Allow new concrete to cure for at least 14 days prior to application.
- Remove all dirt, stains, dust and foreign material.
- Colored concrete should be wet down then 30 parts water to 2 parts hydrochloric acid mixture applied, scrubbed lightly and thoroughly rinsed off.
- For non colored concrete, the same should be done with 20 parts water to 1 part hydrochloric acid solution.
- If an unsealed surface gets wet, allow 24 hours for drying.
- Initial coat 4 - 8 square meters and second coat 7 - 10 square meters per litre, depending on the porosity of the substrate.
- Use a brush, broom or roller.
- For colored concrete or especially smooth concrete, we recommend that the first coat of sealer be diluted with 20% **EVERSOL**.
- 1 or 2 coats should be applied depending on the finish required and the porosity of the substrate.
- Application should not be made when temperature is over 30°C.
- **PAVACRYL** can reduce the non-slip characteristic of a surface, particularly when the surface is smooth. We recommend the use of '**GRIP ENHANCER**' mixed with **PAVACRYL**.
- If using as a COLOR ENHANCER for SANDSTONE it is best to pre-seal area with **SILCOPEL** or **CONSOLIDATE** for best results. Allow pre-sealer 24 - 48 hours to cure before applying **PAVACRYL**.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*