



Manufacturers of BIO-SAFE Technology

Application Data Sheet: **PLUS BIO-SAFE™** NATURAL SEALER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- PLUS BIO-SAFE™ is not suitable for very low porosity surfaces such as polished porcelain or vitrified tiles. For these we recommend PROTEX BIO-SAFE™.
- For low porosity surfaces such as tessellated tile, and some polished stone or Australian made terracotta we recommend PRISTINE BIO-SAFE™.
- We recommend that newly laid surfaces be cleaned with D-SCALE a Phosphoric Acid cleaner prior to sealing, and for acid sensitive surfaces like Marble, Travertine etc. clean with D-GREASE or MISTER CLEAN.
- Any stain, grease or marks on old surfaces should be cleaned off with D-GREASE and the surface should be thoroughly dry and dust free prior to sealing.
- Application - Use a lambs wool applicator, spray, a clean white absorbent cloth or paint brush.
- Apply coats in a cross direction for complete coverage e.g. first coat in north - south direction and the second coating an east - west direction.
- Allow at least 30-60 minutes between coats. Keep surface dry and free of traffic for two hours after application.
- DO NOT pour the sealer directly onto the surface nor allow the sealer to puddle.
- PLUS BIO-SAFE™ is a fast evaporative sealer therefore cover roller tray and keep air contamination to a minimum.
- Always ensure maximum ventilation for best performance.
- Do not allow the sealer to come into contact with painted surfaces, plastic, vinyl etc.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user MUST educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*