



Manufacturers of BIO-SAFE Technology

Application Data Sheet: **PRISTINE BIO-SAFE™** NATURAL STONE SEALER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Ensure surface to be treated is **DRY**, clean, free of residues and other contaminates.
- **DO NOT** thin product or alter formula.
- **APPLY ONLY** when surface temperature is between 5 – 35 degrees C.
- Use lambs wool applicator, sprayer, clean white absorbent cloth or paint brush. (Finer pored surfaces, polish in sealer).
- Apply coats in a cross direction for complete coverage e.g. first coat in a north-south direction and the second coat in an east-west direction.
- Allow 30 - 60 minutes between coats. Keep surface dry and free of traffic for 2 hours after application.
- Do not pour the sealer directly onto the surface nor allow the sealer to puddle.
- If any excess sealer is seen 15 minutes after the final application, polish the surface with a clean white cotton cloth to remove excess product.
- **PRISTINE BIO-SAFE™** is a quick evaporator so cover roller tray and keep minimum amount exposed.
- **Always ensure maximum ventilation.**
- Do not allow the sealer to come into contact with painted surfaces, plastic, vinyl etc.
- Sealer **will not** prevent surface etching or wear and may lighten or darken some surfaces.
- **PRISTINE BIO-SAFE™** will make the maintenance and cleaning of the surface much easier when applied correctly.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*

