



SOLUTIONS

SEALERS FOR STONE & TILE
The Next Generation of Stone Care Products

Manufacturers of BIO-SAFE Technology

NATIONAL PH: 1300 4 STONE

Ph. + 61 7 5437 7714

Fax: + 61 7 5437 7715

E: info@solutionssealers.com.au

W: www.solutionssealers.com.au

ABN: 25 128 656 082

Application Data Sheet: **PROTEX BIO-SAFE™** NATURAL STONE SEALER



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Ensure surface is clean and **DRY**, making sure any cleaning agents have been thoroughly rinsed off.
- We recommend cleaning porcelain with **D-SCALE**, a Phosphoric Acid cleaner to remove grout haze. Any acid sensitive surfaces like marble etc. can be cleaned with either **D-GREASE** an Alkaline Cleaner or **MISTER CLEAN** cream cleanser.
- **DO NOT** thin product or alter formula in any way.
- Apply only at recommended surface temperature between 5 - 35° C.
- Apply a **LIGHT** even coat with a dry absorbent cloth, microfibre mop or lambs wool applicator.
N.B: It is better to apply several **LIGHT** coats than saturate the surface.
- Some more porous surfaces will require 2 - 3 heavier coats. Allow 45 – 60 minutes between coats.
- After applying the **PROTEX BIO-SAFE™** it is normal on some surfaces for residue to be left behind. If this is the case, remove any surface excess with a dry absorbent cloth. This should be done after the sealer has dried but before it has fully cured, between 45 – 60 minutes after sealer has been applied.
- You may also 'BUFF IN' the final **LIGHT** application of **PROTEX BIO-SAFE™** with a white nylon pad or lambs wool buffer. This will help remove excess and 'LOCK' sealer into pores.
- Any stubborn residues can be removed with a white cotton cloth lightly moistened in **PROTEX BIO-SAFE™** or **BIO-SAFE™ THINNERS**, rubbing until dry or simply using **MISTER CLEAN** cream cleanser after a few days.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*