




Manufacturers of BIO-SAFE Technology

## Technical Data Sheet: **PLUS BIO-SAFE™** NATURAL SEALER

---



### Description:

**PLUS BIO-SAFE™** is a high solids state of the art penetrating sealer, specifically designed for porous surfaces. Bio-Safe™ technology allows the sealer to deeply penetrate the surface without the associated health hazards that are in petrol-chemical solvents. These highly durable resins are deposited into the capillaries of the porous surfaces, leaving a barrier against water and oil borne contaminants, with minimal change to the natural appearance of the surface.

---

### Advantages:

- Suitable for internal and external use.
  - GECA approved. <http://www.geca.org.au/product-solutionsSealers.htm>
  - Invisible finish which maintains natural look.
  - Allows grout or tiles to breathe
  - Protects against water borne and oil based stains
  - Higher solids makes it suitable for porous surfaces
  - Non-ozone depleting.
  - Natural fragrance while sealing.
  - Makes cleaning of tiles easier.
- 

### Characteristics:

Colour:	Clear
Weight:	0.88
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	6 – 8 sq m per lt (depending on porosity)

---

### Recommendations:

Terra Cotta  
Sandstone  
Porous Granite  
Porous Limestone  
Clay Pavers  
Concrete Pavers

---

#### Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*

Solutions - Sealers Technical service department Doc: PLUS BIO-SAFE™ TECH DATA.VER.2