



Manufacturers of BIO-SAFE Technology

Technical Data Sheet:

PRISTINE BIO-SAFE™

NATURAL STONE SEALER



Description:

PRISTINE BIO-SAFE™ Natural Sealer is a state of the art solvent based penetrating sealer. It contains scientifically advanced BIO-SAFE™ technology with resins which are renowned for durability. These resins are deposited in the capillaries of porous surfaces – leaving a barrier against water and oil borne contaminants, with minimal change to the natural appearance of the surface. **PRISTINE BIO-SAFE™** is ideal for terracotta and other hard to keep clean porous masonry surfaces.

Advantages:

- Suitable for internal and external use.
- NICNAS recognizes Bio-Safe™ Technology as not detrimental to health.
- GECA approved. <http://www.geca.org.au/product-solutionsSealers.htm>
- Premium long-life Bio-Safe™ product.
- Invisible finish which maintains a natural look.
- Allows grout or tile to breathe which means sealing is possible without lengthy delays.
- Protects against water-borne and oil-based stains.
- Makes cleaning of tiles easier.
- Pleasant natural fragrance while sealing.

Characteristics:

Colour:	Clear
Weight:	0.86
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	5 – 10 sq m per lt (depending on porosity)

Recommendations:

Terra Cotta
Sandstone
Limestone
Slate
Tessellated Tiles
Clay Pavers
Concrete Pavers

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*